

Solid Rivet (Lb) - Length: 3/8", Diameter: 3/32", Universal Head, 2117-T4 Aluminum Alloy

Detail	Characteristic
FASTENER LENGTH	0.365 INCHES MINIMUM AND 0.385 INCHES MAXIMUM
GRIP LENGTH	0.224 INCHES MINIMUM AND 0.244 INCHES MAXIMUM
HEAD HEIGHT	0.040 INCHES MINIMUM AND 0.050 INCHES MAXIMUM
HEAD MAJOR DIAMETER	0.178 INCHES MINIMUM AND 0.196 INCHES MAXIMUM
HEAD STYLE	UNIVERSAL
MATERIAL DOCUMENT AND CLASSIFICATION	QQ-A-430 FED SPEC SINGLE MATERIAL RESPONSE OVERALL
MATERIAL	ALUMINUM ALLOY 2117 OVERALL
SHANK DIAMETER	0.093 INCHES MINIMUM AND 0.097 INCHES MAXIMUM
SHANK STYLE	STRAIGHT
SHEAR STRENGTH	26000 SINGLE POUNDS PER SQUARE INCH
SURFACE TREATMENT DOCUMENT AND CLASSIFICATION	MIL-C-5541 MIL SPEC 1ST TREATMENT RESPONSE OVERALL OR MIL-A-8625 MIL SPEC 2ND TREATMENT RESPONSE OVERALL
SURFACE TREATMENT	OXIDE FILM OVERALL OR ANODIZE OVERALL



Specifications | Note

Specifications —

Inventory	53
Estimated Ship Date	Ships in 1 Business Day
Inventory Note	Need additional stock? Call (855) 995-0804 or email
Rivet Type	Solid
Weight	1 lb
Alternate Part Number	AN470AD3-6
NSN	5320-00-117-6817
NIIN	00-117-6817
Part # Unpunctuated	MS20470AD36
Minimum Order Note	Minimum order is 1. Must order in increments of 1.
Pre-Packaged Bag Quantity	1

Note —

California Residents	Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.
Note	Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.